# Specification Sheet

Part Number: TAG59L-788


Laser Tag Label, 1.5" x 4.0", 14 Per Sheet, PET, White, 3500/pkg

| | |
|---|---|
| **Article Number** | 594-59788 |
| **Type** | TAG59L |
| **Color** | White (WH) |
| **Features & Benefits** | • LaserTags are sheet fed for easy loading and fast printing. • LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing. • LaserTags are printable using toner for long term UV exposure. • LaserTags come in a variety of label sizes and types to fit most applications. |
| **Quantity Per** | pack |

| | |
|---|---|
| **Product Description** | LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers. |
| **Short Description** | Laser Tag Label, 1.5" x 4.0", 14 Per Sheet, PET, White, 3500/pkg |
| **Global Part Name** | TAG59L-788-WH |
| **Width W (Imperial)** | 4.0 |
| **Width W (Metric)** | 101.6 |
| **Thickness T (Metric)** | 64.0 |
| **Height H (Imperial)** | 1.5 |
| **Height H (Metric)** | 38.1 |
| **Material** | Type 788, Polyester (788) |
| **Material Shortcut** | 788 |
| **Adhesive** | Acrylic |
| **Halogen free** | No |
| **Adhesive Operating Temperature** | -40°F to +199°F (-40°C to +93°C) |

| | |
|---|---|
| **Operating Temperature (Metric)** | -40°F to +199°F (-40°C to +93°C) |
| **Reach Complaint(Article 33)** | Yes |
| **ROHS Complaint** | Yes |
| **Package Quantity(Imperial)** | 3500 |
| **Package Quantity (Metric)** | 3500 |
| **Customs Number** | 3919905060 |
| **Labels per Column** | 7 |
| **Labels per Row** | 2 |
| **Weight (Metric)** | 0.521 |
| **Weight (Imperial)** | 1.14 |