









Oct.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



Recommended PCB Layout
(Board thickness : t=1.6±0.1mm)



Packing Diagram(FREE)



- Notes 1. Per tray : 72 Pieces.
2. UL(File No. E52653)
C-UL(File No. E52653)
TUV (Certificate No. R50244085) authorization article.



1	PBT	BLACK, UL94-V0	4	PS	CLEAR
NO.	MATERIAL	FINISH, REMARKS	3	Brass	Tin Plating 1μm min
UNITS mm	SCALE 2 : 1	COUNT	2	Copper Alloy	Contact Area : Au Plating 0.2μm min Lead area : Tin Plating 1μm min Under Plating : Ni Plating 1μm min
APPROVED : KI. AKIYAMA	15.06.03	DRAWING NO.	EDC-342144-27-00		
CHECKED : TS. FUKUSHIMA	15.06.02	PART NO.	DF60-2P-10.16DS(27)		
DESIGNED : TS. KUMAZAWA	15.06.02	CODE NO.	CL680-3016-4-27		
DRAWN : TS. KUMAZAWA	15.06.02				