







1 WHEN THIS CONNECTOR HAS TWO OR THREE CONTACTS, THE LOCK OF CONNECTOR SHALL BE SET AT THE CENTER OF HOUSING. IN CASE THAT THE NUMBER OF CONTACTS IS MORE THAN FOUR, THE TWO LOCKS SHALL BE SET IN ACCORDANCE WITH THE DRAWINGS.

3 ARTICLE DELETED

				2		BRASS 		SURFACE:TIN PLATED 1μm min UNDER PLATING:COPPER PLATED 1μm min											
1		POLYAMIDE		BEIGE (NATURAL) , UL94V-0															
NO.		MATERIAL		FINISH , REMARKS				NO.		MATERIAL		FINISH , REMARKS							
UNITS mm				SCALE 5 : 1				COUNT 4		DESCRIPTION OF REVISIONS DIS-H-006947				DESIGNED MI. SAKIMURA		CHECKED HK. UMEHARA		DATE 12. 06. 14	
 HIROSE ELECTRIC CO. , LTD.						APPROVED :KJ. KATAYOSE				05. 01. 05		DRAWING NO. EDC3-083673-01							
						CHECKED :TY. OMA				05. 01. 05		PART NO. DF13-*P-1. 25DSA							
						DESIGNED :TS. KUMAZAWA				05. 01. 05		CODE NO.							
						DRAWN :TS. KUMAZAWA				05. 01. 05									
																			