

## Honeywell Sensing and Control

Search


[narrow your search](#)

### Products

- Controls Monitoring and Lighting (354)
- Machine Safety (1726)
- Sensors (7074)
- Switches (9814)

### Technology

- Electromechanical (9357)
- Magnetic (538)
- Microstructure (2328)
- Optical/Infrared (1077)
- Thick Film (1764)
- More...

## 600EN-128-C24 Encoders

(Home : Products)



Actual product appearance may vary.

600 Series optical, 128 pulse per revolution, 2-square wave

[Sales & Service](#)
[Distributor Inventory](#)

### Need Help?

[Click here to contact us](#)
[Overview](#)[Specs](#)[Documentation](#)[Application Notes](#)

### Product Specifications

|                       |                                                                                             |
|-----------------------|---------------------------------------------------------------------------------------------|
| Encoder Type          | Optical                                                                                     |
| Pulse Per Revolution  | 128 pulses/revolution                                                                       |
| Dome Switch           | No                                                                                          |
| Output                | 2-square wave, Channel A leads Channel B by 90 ° electrically in counterclockwise direction |
| Electrical Travel     | Continuous                                                                                  |
| Source Voltage Range  | 4.75 Vdc min., 5.0 Vdc nom., 5.25 V max.                                                    |
| Supply Current        | 30 mA                                                                                       |
| Output Voltage        | 2.4 Vdc min. (out high); 0.4 Vdc max. (out low)                                             |
| Pull-up Resistor      | 10 kOhms                                                                                    |
| Operating Speed       | 300 RPM max.                                                                                |
| Operating Torque      | 0,011 N m [1.5 oz in] max.                                                                  |
| Terminal              | PC terminals Type C-24 (vertical mount)                                                     |
| Terminal Strength     | 0,9 kg [2.0 lb]                                                                             |
| Housing Type          | Molded thermoplastic                                                                        |
| Mechanical Travel     | Continuous                                                                                  |
| Rotational Life       | 10 million shaft rotations                                                                  |
| Shaft Axial Force     | 6,8 kg [15 lb] push/pull                                                                    |
| Shaft End Play        | 0,127 mm [0.005 in] max.                                                                    |
| Shaft Radial Play     | 0,254 mm [0.01 in] at 25,4 mm [1 in]                                                        |
| Shaft Material        | Stainless steel                                                                             |
| Shaft Diameter        | 6,35 mm [0.25 in]                                                                           |
| Shaft Length          | 19,05 mm [0.75 in]                                                                          |
| Bushing Material      | Nichel plated brass                                                                         |
| Bushing Diameter      | 9,53 mm [0.375 in] x 32 NEF-2A                                                              |
| Bushing Length        | 9,53 mm [0.375 in]                                                                          |
| Operating Temperature | -40 °C to 65 °C [-40 °F to 149 °F]                                                          |
| Storage Temperature   | -55 °C to 110 °C [-67 °F to 230 °F]                                                         |
| Humidity              | 85% RH at 40 °C [104 °F] 240 hr                                                             |

|                  |                                                              |
|------------------|--------------------------------------------------------------|
| Shock            | 100 G at 6 per MIL-STD-202; Method 213, Condition C          |
| Vibration        | 10 Hz to 2000 Hz, 15 G; MIL-STD-202, Method 204, Condition C |
| Series Name      | 600                                                          |
| Availability     | Global                                                       |
| UNSPSC Code      | 30211929                                                     |
| UNSPSC Commodity | 30211929 Encoders                                            |

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)