Interactive Catalog Supplements Catalog PDFs

If you need detailed product information, or help choosing the right product for your application, see our Interactive Catalog. Use the Interactive Catalog to access the most complete and up-to-date information available.

The Interactive Catalog provides an extensive collection of product specifications, application data, and technical literature that can be searched based on criteria you select.

This PDF catalog information was published in November 2000.



Click this icon to try the Interactive Catalog.

11 West Spring Street Freeport, IL 61032


level and 100,000 feet (amps) 602/622HE1-6 28 VDC 1HE1-6 604/624HE1-6 Resistive 5 7 Inductive Motor

ELECTRICAL RATINGS allips at sea


Gold contacts can be provided with $\frac{1}{2}$ amp inductive and 1 amp resistive at 28 VDC electrical rating.

HE MOUNTING DIMENSIONS (For reference only)

1HE1-6




602HE1-6



604HE1-6 has same dimensions as 602HE1-6, except housing dia. is 1.0/25,4; and housing height is 1.2/30,5.

Key: $\frac{0.00 = mm}{0.00 = inches}$

622HE1-6



624HE1-6 has same dimensions as 622HE1-6, except housing dia. is 1.0/25,4; and housing height is 1.2/30,5.

X-ON Electronics

Authorized Distributor

Click to view similar products for Basic / Snap Action Switches category:

602EN109-RB MAB6B D2VW-01L1B-1 EXHT-AR403 81716512 83160093 831690CR.5.BB 9007AA1 9007C54D 9007C62A2