

CATALOG LISTING
BZ-2RW82272555124-A2
PAGE 1 OF 1
ISSUE 3
REVISIONS
A 0016786
SPK
23NOV05
B 0046794
KNR
10DEC08
RASTER
DRAWN
G J W
1 APR 99
CHECK
J A F
2 APR 99
CHECK
R J
23NOV05
CHECK
R S
10 DEC08
RELEASE NO. PR-24038
REPLACES
X111903-BZ


MICRO SWITCH
a Honeywell Division
FED. MFG. CODE 91929

SWITCH - BASIC

CATALOG LISTING
BZ-2RW82272555124-A2

PRODUCT CODE: AQC9944

WHEN SEARCHING FOR THIS CATALOG LISTING WITHIN HONEYWELL'S INTERNAL SAP SYSTEM, THE LISTING MUST BE ENTERED WITHOUT DASHES(BZ2RW82272555124A2) DUE TO CHARACTER LIMITATIONS IMPOSED BY THE SYSTEM




NOTES

- 1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF $\phi .139$ MAX ON $1.000 \pm .002$ CENTERS
- 2 - SEALED CONSTRUCTION PROVIDES SPLASH RESISTANCE
- 3 - CONTACT MATERIAL : GOLD ALLOY
- 4 - SWITCH WILL WITHSTAND TEMPERATURE OF $250^{\circ} F$

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS	ELECTRICAL DATA		SCALE	NONE	DO NOT SCALE PRINT
	CONTACT ARRANGEMENT SPDT		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		
OPERATING FORCE----- 6 OZ MAX	L22	1A 125 VAC  	ONE PLACE	(.0)	±.030
RELEASE FORCE----- 1 1/2 OZ MIN			TWO PLACE	(.00)	±.015
DIFFERENTIAL TRAVEL-----.003-.020			THREE PLACE	(.000)	±.005
OVERTRAVEL----- .094 MIN			ANGLES		±
	L288 L307 L315	  1A 250V ~ T85 25E3	WEIGHT		