Accessories

Lacking Ring Whenth Metallic boolsed to lighten the plastic locking ring when installing the HW	Accessories				
Longo/LED Removal Tool Robber fool makes impt/ED removal essier DR-56 Anti-Rotation Ring Persents rotation of switches in panel, included with all assembled switches except plot lights) Black rubber plug fills unused 7/8" mounting holes in panel. To rotund panel cutout EW92-Ri Metablic Mounting Black rubber plug fills unused 7/8" mounting holes in panel. To prevent contact between adjacent lead wires when fautions or switches are tightly mounted close together. To prevent contact between adjacent lead wires when fautions or switches are tightly mounted close together. Book Degree of protection: PB6 Used to cover and protect pushbuttons Operating temperature: -00 to +60°C Plastic hinged pollocidable cover to protect pushbuttons or selector switches. (Not intended for E-Stage) Degree of protection: PB6 To prevent contact mounting follows by the panel. Used to mount mount HV series (except Jumbo Mush- community Adaptor Used to provent contact mounting lover from moving due to hoopy wibration tom, unloody, and square units into a larger panel currout unitides both pieces) Used to provent contact mounting lover from moving due to hoopy wibration tom, unloody, and square units into a larger panel currout unitides both pieces) First dued with HVVIB-MQ. Provided with operator lisest between bozel and locking ring. HW92-A30 HW92-A55 HW92-A55 HW92-A55 HW92-A55 First dued with HWVIB-MQ. Plostic locking rut comes with all HW operators & assemblies.		Appearance	Description/Usage	Part Number	
Anti-Rotation Pring Prevents notation of switches in panel, lincluded with all assembled Anti-Rotation Pring Black rubber plug fills unused 7/8" mounting holes in panel. Black rubber plug fills unused 7/8" mounting holes in panel. GB-31 Metallic Mounting Hole Plug Black rubber plug fills unused 7/8" mounting holes in panel. GB-31 West lic Mounting Hole Plug Barrier For plugging unused 7/8" mounting holes in the panel. Tighton the attached locking ring to a torque of 12 king or maximum Degree of protection: PR66 Barrier To prevent contact between adjacent lead wires when buttons or switches are tightly mounted close together. Degree of protection: PR66 Extended Pushbuttons OC-31 Extended Pushbuttons OC-32 Pastic himped pedilockable cover to protect pushbuttons or selector switches. Work intended for E-Stops) Degree of protection: PR65 Tab Terminal Adaptor Tab #250 (6.35 x 0.8mm): Single tab TW474 Mounting Adaptor Used to mount round HMV series (except Jumbo Mush- rount, michody, and square units into a larger panel out out. Includes both piccosal Replacement Safety Used to mount contact mounting lever from moving due to heavy vibration or panel maintenance. (included with all Contact Block Mounting Adaptors) Reset Rod for Contactors (Cverload Sf rod used with HW18-A40. Provided with HW18-A40. Provided with persons. Insert between bozal and locking ring. HWM. WASHER Fix92.1 N HWM2-RS-TK2141 Fix93.2 N Replacement Opera- tor Wesher	Locking Ring Wrench			MW9Z-T1	
Anti-Rotation Ring Prevents rotation of switches in penel, lincluded with all assembled switches accept plot lights] Rubber Mounting Black rubber plug fills unused 7/8" mounting holes in penel. Por plugging unused 7/8" mounting holes in penel. Tighten the attached locking ring to a torque of 12 kg-cm maximum Degree of protection. PB6 Barrier To prevent contact between adjacent lead wires when buttons or switches are sightly mounted close together. Pushbutton Clear Boot Plastic hinged pediociable cover to protect pushbuttons or selector switches, (Not intended for E-Stops) Degree of protection. PB6 Tab Jezso (6.55 x 0.8mm): Single tab Used to rown include, and space untils lint to larger panel our-out, includes both plecas.) Used to rown tround HW series (except Jumbo Mush- rom, unabody, and space units) into a larger panel out-out, includes both plecas.) Used to revent contact mounting lever from moving due to heavy vibration or penel maintenance, included with all Contact Block Mounting Adaptors Provided with operator. Insert between bezel and locking ring. Provided with operator. Insert between bezel and locking ring. Standard (plastic) HW92-LN Brandard (plastic) HW92-LN			Rubber tool makes lamp/LED removal easier.	OR-55	
Black rubber plug fills unused 7/8" mounting holes in panel. QB-31	Anti-Rotation Ring	0		cutout (standard)	
Metallic Mounting For plugging unused 7/8" mounting holes in the panel. Tighten the attached looking ring to a torque of 12 k/g-cm maximum LW92-BM	Dubban Manakan			for round panel cutout LVV9Z-L	
Barrier To prevent contact between adjacent lead wires when buttons or switches are tightly mounted close together. HW-VL1			Black rubber plug fills unused 7/8" mounting holes in panel.	OB-31	
Pushbutton Clear Boot Used to cover and protect pushbuttons Operating temperature: -50 to +60°C Padlock Cover Padlock Cover Padlock Cover Padlock Cover Padlock Cover Tab #250 (6.35 x 0.8mm): Single tab Used to mount round HW series (except Jumbo Mushroom, unibody, and square units) into a larger panel cut-out, lincludes both pieces) Replacement Safety Lever Lock Reset Rod for Contactors Overload Provided with operator. Insert between bezel and locking ring. Used to mount comes with all HW operators & assemblies. Plastic locking nut comes with all HW operators & assemblies.			locking ring to a torque of 12 kfg-cm maximum	LW9Z-BM	
Padlock Cover Padlock Cover Plastic hinged padlockable cover to protect pushbuttons or selector switches. (Not intended for E-Stops) Degree of protection: IP65 Tab #250 (6.35 x 0.8mm): Single tab Used to mount round HW series (except Jumbo Mushroom, unibody, and square units) into a larger panel cut-out. (includes both pieces) Replacement Safety Lever Lock Reset Rod for Contactors Overload Provided with uperator. Insert between bezel and locking ring. Plastic locking nut comes with all HW operators & assemblies.	Barrier	6.0		HW-VL1	
Padlock Cover Plastic hinged padlockable cover to protect pushbuttons or selector switches. (Not intended for E-Stops) Degree of protection: IP65 Tab Terminal Adapter Used to mount round HW series (except Jumbo Mushroom, unibody, and square units) into a larger panel cut-out. (includes both pieces) Replacement Safety Lever Lock Used to prevent contact mounting lever from moving due to heavy vibration or panel maintenance. (included with all Contact Block Mounting Adaptors) HW9Z-RS-TK2141 Replacement Operator Washer Provided with operator. Insert between bezel and locking ring. Plastic locking nut comes with all HW operators & assemblies.			Used to cover and protect pushbuttons	Flush Pushbuttons OC-31	
Padlock Cover Switches. (Not intended for E-Stops) HW9Z-KL1	Boot			Extended Pushbuttons OC-32	
Used to mount round HW series (except Jumbo Mush- room, unibody, and square units) into a larger panel cut-out. (includes both pieces) 22 to 30mm HW9Z-A30	Padlock Cover		switches. (Not intended for E-Stops)	HW9Z-KL1	
Mounting Adaptor room, unibody, and square units) into a larger panel cut-out. (includes both pieces) Replacement Safety Lever Lock Used to prevent contact mounting lever from moving due to heavy vibration or panel maintenance. (included with all Contact Block Mounting Adaptors) HW9Z-LS Reset Rod for Contactors Overload Find used with HW1B-M0. Provided with operator. Insert between bezel and locking ring. HWM-WASHER Standard (plastic) HW9Z-LN Plastic locking nut comes with all HW operators & assemblies.	Tab Terminal Adapter		Tab #250 (6.35 x 0.8mm): Single tab	TW-FA1	
Replacement Safety Lever Lock Reset Rod for Contactors Overload Replacement Operator Washer Replacement Locking Replacement Replace	AA .: A1 .			HW9Z-A30	
Reset Rod for Contactors Overload Replacement Operator Washer Provided with operator. Insert between bezel and locking ring. Provided with operators & assemblies.	Mounting Adaptor			HW9Z-A25	
Replacement Operator Washer Provided with operator. Insert between bezel and locking ring. HWM2-RS-1RZ141 HWM-WASHER Replacement Locking Ring Plastic locking nut comes with all HW operators & assemblies.		1		HW9Z-LS	
Replacement Locking Ring Plastic locking nut comes with all HW operators & assemblies. Replacement Locking Ring Plastic locking nut comes with all HW operators & assemblies.		6-	5" rod used with HW1B-M0.	HW9Z-RS-TK2141	
Replacement Locking Plastic locking nut comes with all HW operators & assemblies.		0	Provided with operator. Insert between bezel and locking ring.	HWM-WASHER	
DIIII		0	Plastic locking nut comes with all HW operators & assemblies.	Standard (plastic) HW9Z-LN	
				Optional (metal) HW9Z-LNM	
Switch Cover (Square) Used only with round or square flush pushbuttons. HW9Z-K1 (spring return) HW9Z-K11 (maintained cover)			Used only with round or square flush pushbuttons.		
Replacement Keys Pair of Keys (#231) HW9Z-SKP	Replacement Keys		Pair of Keys (#231)	HW9Z-SKP	