










SR3P Sockets


SR3P-05

Style	11-pin octal, snap-mount/surface mount
Terminal	M3.5 screws with captive wire clamp
Wire Size	Maximum up to 2-#12AWG
Electrical Rating	300V, 10A
Compatible Relay	RR3PA, RR2KP
Compatible Timer	GT3 (11-pin), RTE-P2
Hold-Down Spring	SR3B-02F1 for RR3P; SR3P-06F3 for RR2KP
Hold-Down Clip	SFA-203 (Timers)


Terminal Arrangements
(top view)

SR3P-05C Fingersafe






Style	11-pin octal, snap-mount/surface mount
Terminal	M3.5 screws with captive wire clamp, fingersafe
Wire Size	Maximum up to 2-#12AWG
Electrical Rating	300V, 10A
Compatible Relay	RR3PA, *RR2KP (*latching relay)
Compatible Timer	GT3 (11-pin), RTE-P2
Hold-Down Spring	SR3B-02F1 for RR3PA; SR3P-06F3 for RR2KP
Hold-Down Clip	SFA-203 (Timers)



F


SR3P-06

Style	11-pin octal, snap-mount/surface mount
Terminal	M3.5 screws with captive wire clamp
Wire Size	Maximum up to 2-#12AWG
Electrical Rating	300V, 10A
Compatible Relay	RR3PA, *RR2KP (*latching relay)
Compatible Timer	GT3 (11-pin), RTE-P2
Hold-Down Spring	SR3B-02F1 for RR3PA; SR3P-06F3 for RR2KP
Hold-Down Clip	SFA-202 (Timers)



1. For socket mounting accessories, see page F-24.
2. For hold-down clip/spring selections, see page F-4.