

SEARCH OUR
PRODUCTS

aluminum
electrolytic &
organic
semiconductor

film

power film

tantalum
ceramic

TECH TOOLS



NEW PRODUCTS

Aluminum Electrolytic Capacitors

+85°C Reduced Size Snap-Mount Aluminum Electrolytic Capacitors

Part Number: 227LBB400M2CF

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[LBB document \(PDF\)](#)



Electrical Specifications

Capacitance: 220.0 μ F

Tolerance: -20 %, +20 %

Dissipation Factor: 0.15 at 120 Hz

ESR: 1,130.36 milliohms at 20° C and 120 Hz

Impedance:

--

--

Impedance Ratios:

4.0 at -25°C/20°C

at -40°C/20°C

Load Life:

3000 Hours at 85°C with 100% of rated voltage and
with 100% of rated ripple current

Temperature Range: -40°C to +85°C

WVDC: 400 volts DC

SVDC: 450. volts DC

Leakage Current:

1,760.0 μ A after 5 Minutes

Ripple Current:

1.64 A at 120 Hz and 85°C

Physical Specifications


Diameter (D): 25.0 mm + 1.0 mm

Length (L): 40.0 mm + 2.0 mm

Lead Wire Diameter (d): 1.5 mm + 0.5 mm

Lead Spacing: 10.0 mm +/- 1.0 mm

Lead Length: 4 mm



Add To Sample Cart
(You can always remove it later)