
Intel® Xeon® Processor E5-2658 v2
 (25M Cache, 2.40 GHz)

[Add to Compare](#)



[Visit the Embedded Design Center >](#)

QUICK LINKS

- [Products formerly Ivy Bridge](#)
- [Download Datasheet](#)
- [Search Distributors](#)
- [Support Overview](#)
- [Search all of intel.com](#)

PCN/MDDS Information

SR1A0
 929993: [PCN](#) | [MDDS](#)


SPECIFICATIONS

- [Essentials](#)
- [Memory Specifications](#)
- [Expansion Options](#)
- [Package Specifications](#)
- [Advanced Technologies](#)
- [Intel® Data Protection Technology](#)
- [Intel® Platform Protection Technology](#)

[ORDERING / SSPECS / STEPPINGS](#)

SPECIFICATIONS

Essentials

Status	Launched
Launch Date	Q3'13
Processor Number	E5-2658V2
# of Cores	10
# of Threads	20
Clock Speed	2.4 GHz
Max Turbo Frequency	3 GHz
Cache	25 MB
Intel® QPI Speed	8 GT/s
# of QPI Links	2
Instruction Set	64-bit
Instruction Set Extensions	Intel® AVX
Embedded Options Available	 Yes
Lithography	22 nm
Scalability	2S Only
Max TDP	95 W
VID Voltage Range	0.65–1.30V
Recommended Customer Price	










Memory Specifications

Max Memory Size (dependent on memory type)	768 GB
--	--------

# of Memory Channels	4
Max Memory Bandwidth	59.7 GB/s
Physical Address Extensions	46-bit
ECC Memory Supported ‡	 Yes

Expansion Options

PCI Express Revision	3.0
PCI Express Configurations ‡	x4, x8, x16

Max # of PCI Express Lanes	40
Package Specifications	
Max CPU Configuration	2
T _{CASE}	75°C
Package Size	52.5mm x 45mm
Sockets Supported	FCLGA2011
Low Halogen Options Available	See MDDS
Advanced Technologies	
Intel® Turbo Boost Technology ‡	2.0
Intel® vPro Technology ‡	 Yes
Intel® Hyper-Threading Technology ‡	 Yes
Intel® Virtualization Technology (VT-x) ‡	 Yes
Intel® Virtualization Technology for Directed I/O (VT-d) ‡	 Yes
Intel® VT-x with Extended Page Tables (EPT) ‡	 Yes
Intel® 64 ‡	 Yes
Idle States	Yes
Enhanced Intel SpeedStep® Technology	 Yes
Intel® Demand Based Switching	 Yes
Thermal Monitoring Technologies	Yes
Intel® Flex Memory Access	No
Intel® Identity Protection Technology ‡	No
Intel® Data Protection Technology	
AES New Instructions	 Yes
Secure Key	Yes
Intel® Platform Protection Technology	
Trusted Execution Technology ‡	 Yes
Execute Disable Bit ‡	Yes

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

For benchmarking data see <http://www.intel.com/performance>.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.


Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading> for more information including details on which processors support Intel® HT Technology.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

Check <http://ipt.intel.com/> for systems that support Intel® Identity Protection Technology (Intel® IPT).

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

 [Send us your feedback!](#)