

[Home](#) | [Sign In](#) | [Site Map](#) | [Contact](#)

SEARCH

[About ITT](#)[Products](#)[Design Center](#)[Literature](#)[News & Events](#)[Search Tools](#)[Global Sales Support](#)[Home](#) > [Search Tools](#) > [ITT Part Number](#)

ITT Part Number Search

Enter Part Number:

PART NUMBER:192926-0470

Product Family

Trident

Product Group

Ringlock

Component

Connector

Sealed

No

Packaging

Single

Connector Material

Plastic

Circular

Shape	
Number of Positions	19
Gender	Receptacle
Contacts to be Fitted	Pin
Mounting Style	Flange Mount
Shell Size	16
Operating Voltage	250 V RMS
Contact Current Rating	depends on contact used
Operating Temperature	-55 °C to 105 °C
Insulation Resistance	5000 M ohms at 500 V DC
Bayonet Pin Material	Stainless Steel
Bayonet Pin Support Band Material	High Strength Copper Alloy
Bayonet Pin Support Band Finish	Nickel
Flammability	UL 94V-0
For more information	Contact Cannon Sales Department 31,50 (1.240) max.

Dimension A	
Dimension B	2,30 ±0,15 (.091 ±.005)
Dimension C	11,35 ±0,20 (.447 ±.007)
Dimension D	Ø25,40 ±0,15 (1.000 ±.005)
Dimension E	24,20 ±0,15 (.953 ±.005)
Dimension F	30,50 ±0,25 (1.200 ±.009)
Nomenclature	TR1619RMS1NB
Dimension G	Ø3,25 ±0,10 (.128 ±.003)
Dimension H	Ø28,10 ±0,10 (1.106 ±.003)
Dimension J	Ø24,60 ±0,10 (.968 ±.003)
Accessory Thread	15/16-20 UNEF
Note 1	Dimension ØJ = Flange in Front of Panel. Dimension ØH = Flange at Rear of Panel.
Note 2	Contact Cavity Arrangement - Mating Face View Standard Plug (Mating Face View Reversed Plug is Mirror Image)
Footnote	Dimensions are in mm (inch). Dimensions are subject to change.







