

[Home](#) | [Sign In](#) | [Site Map](#) | [Contact Us](#)

Cannon VEAM BIW

SEARCH [About ITT](#)[Products](#)[Design Center](#)[Literature](#)[News & Events](#)[Search Tools](#)[Global Sales Support](#)[Home](#) > [Search Tools](#) > [Part Number](#)

Part Number Search

You Searched For:

Note: Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS. ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Global Sales Locator" located either to the right of this data or at the top of every page.

[Sales Support](#)[Product Overview](#)[Stock Check](#)[Product Home](#)

Our Catalog Part Number: TR1823RMS1NB

Our Global Manufacturing Part Number: 192990-1350

Brand: Cannon Product Category: Trident Product Line: Trident Series: TR



YES RoHS compliant =

material restrictions of lead, cadmium, hexavalent chromium, mercury, poly bromated biphenyl ether (PBB) and poly bromide diphenyl ether (PBDE) according to directive 2002/95/EC

NO RoHS compatible = Compatible with lead free soldering process

Product Datasheet

Series

Trident Ringlock

Operating Voltage

Up to 250 V ac rms

Up to 380 Vac rms (Size 1807 only)

Contact Current Rating

Up to 13 A

Operating Temperature

-55°C to +105°C

Insulation Resistance

5000 Megaohms at 500 V dc

Durability

Up to 500 Mating Cycles

Sealing

Up to IP65

Flammability Rating

UL94-V0

Materials and Finishes

Connector Body: Black Nylon

Coupling Ring: Nickel Plated Copper Alloy

Bayonet Pins: Stainless Steel

Bayonet Pins Support Band: Nickel Plated Copper Alloy

Shell Size

18

Number of Contacts

23

Type

Receptacle

Contact Type

Accepts Male Contacts

Mounting Style

Standard

Material

Nylon

Colour

Black

[Home](#) | [About ITT](#) | [Products](#) | [Design Center](#) | [Literature](#) | [News & Events](#) | [Search Tools](#) | [Global Sales Support](#)[Channel Partners Sign-In](#)[Legal Disclaimer](#) | [Privacy Policy](#) | [Terms & Conditions](#) |  [Provide Website Feedback](#)

© 2010 ITT Corporation. All rights reserved.