




NOTES:

1. LED includes integrated diode for reverse voltage protection.
2. LED includes integrated resistor for current limiting.

TYPICAL ELECTRICAL & OPTICAL OPERATING CHARACTERISTICS

(Ta = 25 degree C)

PART NUMBER	EMITTING COLOR	AMPERAGE mA	VOLTAGE Vdc	LUMENS	COLOR COORDINATES
LE-0603-02R	RED	20mA	12.0	2.00	630nm
LE-0603-02Y	YELLOW	20mA	12.0	2.00	595nm
LE-0603-02G	GREEN	20mA	12.0	9.00	525nm
LE-0603-02B	BLUE	20mA	12.0	2.00	470nm
LE-0603-02W	WHITE	20mA	12.0	10.00	x = 0.29 y = 0.28

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION TITLE LED FESTOON LAMP					
C	CHANGE DIA. TO 10.5 MAX.	11/10/09	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.				
B	CHANGE MOL TO 43.0 MAX.	1/22/09	L. WENGSTROM	L.R.	11/10/09	A	55335	LE-0603-02				
A	CHANGE CHARTS & ADD NOTES	8/25/08										
	ENGR. RELEASE & CANCEL PL-0603-02-1 TO -5	7/5/06										
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE		RELEASED DATE	REVISION DATE	REV. NO.	SHEET	
						NONE		7/5/06	11/10/09	C	1 OF 1	