


A767, Polymer Aluminum, 68 uF, 20%, 63 VDC, -55/+105°C

**Dimensions**

D	10mm +/-0.5mm
L	12.6mm +/-0.3mm
W	0.8 - 1.1mm
F	0.2mm MAX
A	10.3mm +/-0.2mm
B	10.3mm +/-0.2mm
C	11mm +/-0.2mm
G	0.35mm +/-0.2mm
P	4.6mm +/-0.2mm

Packaging Specifications

Packaging:	T&R, 380mm
Packaging Quantity:	400

General Information

Series:	A767
Dielectric:	Polymer Aluminum
Style:	SMD Can
Description:	Surface Mount, Polymer Aluminum
RoHS:	Yes
Lead:	V-Chip
AEC-Q200:	No

Specifications

Capacitance:	68 uF
Capacitance Tolerance:	20%
Voltage DC:	63 VDC, 72 VDC (Surge)
Temperature Range:	-55/+105°C
Rated Temperature:	105°C
Life:	2000 Hrs
Resistance:	30 mOhms (100kHz 20C)
ESR/Impedance at 100kHz:	30 mOhms
Ripple Current:	2450 mAmps (100kHz 105C)
Leakage Current:	856 uA (2min 20°C)
High Temperature Solder:	No