

Electronic Components
KEMET
CHARGED.®

Technical drawing of the E-Label showing front and side views with dimensions:

- Front View (Left):**
 - Overall width: 29 max.
 - Bottom flange thickness: 10
 - Bottom flange width: 17
- Side View (Right):**
 - Overall height: 70
 - Label height: 53 max.
 - Label width: 53 max.
 - Top flange thickness: 4.8
 - Bottom flange thickness: 4.8 ± 6.8*
 - Mounting holes: 5-M4
 - Internal dimensions: 15.5, 26, 60.5

Dimensions	
L	70mm NOM
W	53mm MAX
H	29mm MAX
Lead	Screw Terminals

Packaging Specifications	
Packaging:	Tray, Box
Packaging Quantity:	30
Weight:	160 g

General Information	
Series:	GT
Style:	Metal Box
Description:	Noise Filters
RoHS:	Yes
Miscellaneous:	35 K Self-Temperature Rise Max.
Lead:	Screw Terminals

Specifications	
Voltage AC:	250 VAC
Ripple Current:	5 A (AC/DC)
Temperature Range:	-25/+55°C
Voltage:	250 VDC, 1500 VAC Withstanding Voltage 1 Min. Line to Ground
Leakage Current:	0.5 mA MAX (250 V 60 Hz)
Resistance:	300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground

Electronic Components
KEMET
CHARGED®