
KEMET Part Number: PEH200PO5220MU2

(A351QM223M100A)



Capacitor, aluminum, 0.022 F, +/-20% Tol, -40/+85C, 100VDC@85° C



Dimensions (mm)			
Symbol	Dimension	Tolerance	
D	66.6	+/-1	
L	109.2	+/-1	
S	28.5	+/-0.5	
F	15	+/-0.5	
G	13	NOM	
M	5		
Т	7	+/-0.5	

Notes:

-D and L Dimensions include sleeving

General Information	
Supplier:	KEMET
Part Type Description:	Computer Grade Aluminum Electrolytic
Style:	Computer Grade
Lead Type:	Oval Threaded Inserts- M5
Mounting Type:	Clip- PYC6043

Specifications		
Capacitance:	0.022 F	
Tolerance:	+/-20%	
Rated Temperature:	85° C	
Voltage @ rated temp:	100VDC	
Life @ rated temp:	12500 Hrs	
RoHS:	Yes	
Low Z/ESR:	Yes	
Temperature Range:	-40/+85C	
ESR at 100Hz @ room temp:	15 mOhm	
ESR at 120Hz @ room temp:	14 mOhm	
ESR at 100kHz @ room temp:	13 mOhm	
Leakage Current:	6 mA	
Leakage Condition:	5min/20c	
Impedance @ 10kHz:	13 mOhm	
Impedance @ 100kHz:	18 mOhm	
Ripple 100Hz @ rated temp:	19.3 A	
Ripple 120Hz @ rated temp:	19.8 A	
Ripple 10kHz @ rated temp:	19.7 A	
Ripple 10kHz @ alt temp:	30.1 A	
Ripple 10kHz alt temp:	40	

Packaging Specifications		
Package Kind:	Bulk	
Package Quantity:	12	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

