
KEMET Part Number: PME295RB4470MR30

(P295BQ472M440A)



Capacitor, film, 4700 pF, +/-20% Tol, -40/+115C, Safety: Y1, 480VAC, Lead Spacing=15 mm



| Dimensions (mm) | | |
|-----------------|-----------|-----------|
| Symbol | Dimension | Tolerance |
| L | 18 | MAX |
| Н | 16 | MAX |
| Т | 8.5 | MAX |
| S | 15 | +/-0.4 |
| LL | 30 | +5 |
| G | 0.5 | NOM |
| F | 0.8 | +/-0.05 |

| Packaging Specifications | |
|--------------------------|------|
| Package Kind: | Bulk |
| Package Quantity: | 400 |

| General Information | | |
|---------------------------|-------------------------------|--|
| Supplier: | KEMET | |
| Miscellaneous Electrical: | Ceramic Capacitor replacement | |

| Specifications | |
|-----------------------------|-------------------------|
| Capacitance: | 4700 pF |
| Rated Temperature: | 115° C |
| Voltage AC: | 480VAC |
| Tolerance: | +/-20% |
| Body Type: | Radial Box |
| Dielectric: | Metallized Paper |
| Application: | Safety: Y1 |
| Temperature Range: | -40/+115C |
| Electrical Name (Other): | Self Resonant Frequency |
| Electrical Value (Other): | 22 |
| Electrical Units (Other): | mHz |
| Dissipation Factor @ 1 kHz: | 1.3% |
| Insulation Resistance: | 12 GOhm |
| Maximum dVdT: | 2000v/us |

| Agency Approvals | | |
|------------------|-------------|--|
| Approvals: | ENEC,UL,cUL | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

