


KEMET, RG, EMI/RFI Filters, Noise Suppression, 250 VAC, 250 V, 8 A



General Information

Series:	RG
Style:	Metal Cylinder
Description:	Noise Filters
RoHS:	Yes
Qualifications:	TUV
Miscellaneous:	55 K Self-Temperature Rise Max.
Lead:	Threaded Studs M8

Specifications

Voltage AC:	250 VAC
Ripple Current:	8 A (AC/DC)
Temperature Range:	-25/+55°C
Voltage:	250 VDC, 1500 VAC Withstanding Voltage 1 Min. Line to Ground
Leakage Current:	1 mA MAX (250 V 60 Hz)
Resistance:	100 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground

Dimensions

D	50mm NOM
L	90mm NOM
LL	13mm NOM
L1	12mm NOM
Lead	Threaded Studs M8

Packaging Specifications

Packaging:	Tray, Box
Packaging Quantity:	25
Weight:	320 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.