

0 0 0 0 0 0 0 0 0 6

FEED DIRECTION

TAPE AND REEL SPECIFICATIONS:

Ø.500 [Ø12.7] MIN.

HOLE THRU

4. TAPE: MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER ANSI/EIA-481 STANDARD

.945 [24.00]

5. REEL: 15.0 [380.8] DIA. 500 PIECES PER REEL

6. PICK-UP CAP APPLIED TO EACH CONNECTOR FOR VACUUM PICK AND PLACE REF.

.016 [0.4]

REF.

		KEYSTONE ELECTRONICS CORP. www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500			
	CONTACT WAS COPPER ALLOY HOUSING WAS PA66		SM TOP ENTRY CONNECTOR (3 CIRCUITS)		
10.09.19	CHANGE AS PER ECN 19-078	С	MATERIAL AS NOTED		
8.29.19	CHANGE AS PER ECN 19-075	В	FINISH	DRN BY NT	3.07.16
	UPDATE MTG DETAIL		AS NOTED	APP'D LN	SCALE 4X
8.08.19	CHANGE AS PER ECN 19-065	A	TOLERANCES INCH [MM] CODE DECIMAL ± .005 [± 0.13]	DWG NO.	
DATE	DESCRIPTION	REV.	ANGULAR ± 1° C	(974