



P.C. MOUNTING





Specifications:

Contact rating: max.: 0.4VA, 48V AC/DC / max. 50mA

min.: 1µA, 20mV AC/DC

Contact resistance: 50mOhm max.

Insulation resistance: 500MOhm min. at 250V DC

Dielectric strength: 50V, 50Hz for duration of 1 minute

Operating temperature: -20°C to +85°C
Mechanical life: min. 60 000 cycles

Soldering conditions: auto-soldering: max.: 260 +/-5°C, 5 +/-1.0sec.

Mounting: on pc-board

Contacts: phosphor bronze gold plated over nickel barrier

Terminals: PC terminals, crimped

Material: Case: PBT, meets UL94V-0, washable

Metal parts: nickel plated brass

UL file number: E140532

X	Switch function				
D	on - on				
Е	on - off - on				
F	mom - on				
G	mom - off - mom				
Н	mom - off - on				

Lever position:

For code F and H: "mom" is on the right side when looking at the marking side.

The closed contacts are opposite to the lever position.



Tolerances:			Date	Name					
			08/09	dr	! <u>. —</u> _				
					ATE 1 x-VM / ATE 2 x-VM				
					witch 30 15 35			Page	
			kni†	tter-s			35	raye	
						00		1/1	
Modifications	Date	Name							