





P.C.B. LAYOUT



Specifications:

Contact rating:	switching: 25mA, 24V DC non-switching: 100mA
Contact resistance:	100mOhm max.
Insulation resistance:	1 000MOhm min. at 100V DC
Dielectric strength:	250V AC, 50Hz for the duration of 1 minute
Operating temperature:	-25°C to +70°C
Storage temperature:	-40°C to +85°C
Mechanical life:	2 000 cycles
Soldering conditions:	260 +/-5°C, 5 +/-5sec.
Construction:	washable
Material:	Terminals: tin plated over nickel Case / rotor: PBT, UL94V-0



Tolerances: 0-1: ± 0.03 mm 1-4: ± 0.05 mm 4-16: ± 0.07 mm			Date	Name	DRR 21xxx-1	
			02/12	dr		
					30 25 46	
			knitter-switch			Page
						1/2
Modifications	Date	Name				

		real BCD-coded			
		1	2	4	8
10 P o s i t i o n s	0				
	1	•			
	2		•		
	3	•	•		
	4			•	
	5	•		•	
	6		•	•	
	7	•	•	•	
	8				•
	9	•			•

		invers BCD-coded			
		1	2	4	8
10 P o s i t i o n s	0	•	•	•	•
	1		•	•	•
	2	•		•	•
	3			•	•
	4	•	•		•
	5		•		•
	6	•			•
	7				•
	8	•	•	•	
	9		•	•	

		real hex-coded			
		1	2	4	8
16 P o s i t i o n s	0				
	1	•			
	2		•		
	3	•	•		
	4			•	
	5	•		•	
	6		•	•	
	7	•	•	•	
	8				•
	9	•			•
	A		•		•
	B	•	•		•
	C			•	•
	D	•		•	•
	E		•	•	•
	F	•	•	•	•

		invers hex-coded			
		1	2	4	8
16 P o s i t i o n s	0	•	•	•	•
	1		•	•	•
	2	•		•	•
	3			•	•
	4	•	•		•
	5		•		•
	6	•			•
	7				•
	8	•	•	•	
	9		•	•	
	A	•		•	
	B			•	
	C	•	•		
	D		•		
	E	•			
	F				

xxx	Code	Rotor
010	real BCD-coded, 10pcs.	white
110	invers BCD-coded, 10pcs.	red
016	real hex-coded, 16pcs.	white
116	invers hex-coded, 16pcs.	red



Tolerances: 0-1: ±0.03mm 1-4: ±0.05mm 4-16: ±0.07mm			Date	Name	DRR 21xxx-1
			02/12	dr	
			knitter-switch		30 25 46
					Page
					2/2
Modifications	Date	Name			