




PANEL MOUNTING



CONTACT ARRANGEMENT

code for x	function	toggle towards keyway	toggle opposite to keyway
D	On-On	1-2	2-3
F	Mom-On		

code for x	function	toggle towards keyway	toggle in center	toggle opposite to keyway
E	On-Off-On			
G	Mom-Off-Mom	1-2	open	2-3
H	Mom-Off-On			

Specifications:

Contact rating:

3A, 250V AC / 6A, 125V AC
4A, 30V DC / 5A, 12V DC
6A, 6V DC

Contact resistance:

20mOhm max.

Insulation resistance:

1 000MOhm min. at 500V DC

Dielectric strength:

1 500V, 50Hz for the duration of 1 minute

Operating temperature:

-45°C to +140°C

Mechanical life:

min. 100 000 cycles

Soldering conditions:

hand-soldering: max.: 420°C, 3sec., 60W
auto-soldering: max.: 270°C, 5sec.

Mounting instruction:

max. torque: 137Ncm

IP rating:

IP67

Material:

Terminal / contact: brass, silver plated
Case: DAP

Housing: stainless steel, CNS9265

Bushing: copper alloy, C3604BD nickel plated

Actuator: copper alloy, C3604BD chrome plated

Included accessories:

1 pc. nut 15/32-32, nickel plated, 14mm wrench size
1 pc. tooth washer
1 pc. O-ring, silicone

Compliance: RohS II (2011/65/EU)

Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm			Date 05/09	Name dr	MTW 106 x	
			knitter-switch		30 18 26	
					Page	
					1/1	
Modifications	Date	Name				