

HEIDI-RS

~8° spot beam

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	11.7 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
HEIDI-RS	Single lens	PMMA	clear	
HEIDI-TAPE	Tape	PU tape	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA12537_HEIDI-RS	Single lens	3264	204	204	11.1
» Box size: 480 x 280 x 300 mm					





This drawing is our property.
 It can't be reproduced
 or communicated without
 our written agreement.



Ledil Oy
 Joensuukatu 13
 FIN-24100 SALO
 Finland

DRAWING TITLE

Datasheet Heidi-Series Ass'y

DRAWN BY
ah

DATE
1.2.2012

CHECKED BY

DATE

SIZE

A4

DRAWING NUMBER

REV

2

DESIGNED BY

DATE

SCALE

2:1

WEIGHT (g)


SHEET

1/1


PHOTOMETRIC DATA (MEASURED):





LED XP-G2
FWHM 10.0°
Efficiency 94 %
Peak intensity 20 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-G3
FWHM 12.0°
Efficiency 94 %
Peak intensity 13 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-L HD
FWHM 15.0°
Efficiency 89 %
Peak intensity 8.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON A
FWHM 11.0°
Efficiency 87 %
Peak intensity 15.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED LUXEON Rebel
FWHM 8.0°
Efficiency 88 %
Peak intensity 26 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LUMILEDS

LED LUXEON Rebel ES
FWHM 11.0°
Efficiency 86 %
Peak intensity 15.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LUMINUS

LED SST-10-B130
FWHM 8.0°
Efficiency 96 %
Peak intensity 27.9 cd/Im
LEDs/each optic 1
Light colour Blue
Required components:



NICHIA



LED NVSW219D
FWHM 11.0°
Efficiency 94 %
Peak intensity 14.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):




LED NVSW319B
FWHM 13.0°
Efficiency 94 %
Peak intensity 11.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NVSW3x9A
FWHM 13.0°
Efficiency 92 %
Peak intensity 9.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NWSx229A
FWHM 16.0°
Efficiency 87 %
Peak intensity 7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSLOM SSL 150
FWHM 7.0°
Efficiency 89 %
Peak intensity 28.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED PLPVEC2 850A
FWHM 6.0°
Efficiency %
LEDs/each optic 1
Light colour IR
Required components:



SEOUL
SEMICONDUCTOR

LED Z5M3
FWHM 11.0°
Efficiency 94 %
Peak intensity 12.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SEOUL
SEMICONDUCTOR


LED Z8Y22P
FWHM 12.0°
Efficiency 94 %
Peak intensity 10.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (SIMULATED):



LED XP-G2 HE
FWHM 12.0°
Efficiency 95 %
Peak intensity 12 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON IR Domed 150
FWHM 11.0°
Efficiency 94 %
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON IR Domed 90
FWHM 11.0°
Efficiency 94 %
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON R
FWHM 11.0°
Efficiency 92 %
Peak intensity 16.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED LUXEON SunPlus 20 Line (120 deg)
 FWHM 8.0°
 Efficiency 96 %
 Peak intensity 30.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED LUXEON SunPlus 20 Line (150 deg)
 FWHM 7.8°
 Efficiency 93 %
 Peak intensity 29.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED LUXEON SunPlus 20 Line (150 deg)
 FWHM 8.0°
 Efficiency 92 %
 Peak intensity 28.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED LUXEON SunPlus 35 Line
 FWHM 7.8°
 Efficiency 94 %
 Peak intensity 31.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




PHOTOMETRIC DATA (SIMULATED):




LED NV4WB35AM
FWHM 16.0°
Efficiency 96 %
Peak intensity 8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NVSxE21A
FWHM 10.0°
Efficiency 94 %
Peak intensity 19.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NVSxx19B/NVSxx19C
FWHM 12.0°
Efficiency 95 %
Peak intensity 15 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSCONIQ P 3737 Flat
FWHM 10.0°
Efficiency 96 %
Peak intensity 16.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):

OSRAM

Opto Semiconductors


LED OSLON Black
FWHM 11.0°
Efficiency 93 %
Peak intensity 16.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM


Opto Semiconductors

LED OSLON Black Flat
FWHM 7.3°
Efficiency 94 %
Peak intensity 38.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG

LED LH351D
FWHM 16.0°
Efficiency 94 %
Peak intensity 8.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)