

# PRODUCT DATASHEET Iris series

last update 4/7/2012





## Ordering number FCN12076\_IRIS-SCREW

Family Iris Type Pack LED XP-G Color Black Diameter 38 mm Height 26.9 mm Style Round PMMA Optic Material PC Holder Material

Screw, pin, glue Fastening

Ready Status

#### Ordering number FCA12077\_IRIS

Family Type Assembly LED XP-G Color Black Diameter 38 mm Height 27.1 mm Style Round **PMMA** Optic Material Holder Material PC

Fastening Screw, pin, tape

Status Ready

**FWHM** 6 degrees Efficiency 95 % cd/lm Gerber File Available

**FWHM** 

cd/lm

Efficiency

Gerber File

6 degrees

Available

95 %

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



# PRODUCT DATASHEET Iris series

CREE

last update 4/7/2012

### GENERAL INFORMATION

- Product series especially designed & optimized for XP-G series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Lens material optical grade PMMA with high UV and temperature resistance. Allows use of high current and temperature conditions.

Please find more information about used material from below: http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94\_Yellow%20Card.pdf http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf - Optic holder molded by high quality PC material (120 dergees of Celcius / 248 degrees of Fahrenheit).

