

## SUMMARY

### # Wires

|      |   |
|------|---|
| Coax | 1 |
|------|---|



*Image is for illustrative purpose only*

|                  |                |
|------------------|----------------|
| Series           | 00             |
| Termination type | Male crimp     |
| IP rating        | 50             |
| AWG wire size    | 0.00 - 0.00    |
| Cable Ø          | 0.00 - 3.00 mm |
| Status           | active         |

### Download

[Request a quote](#)

[Catalog](#)

## TECHNICAL DETAILS

### Mechanics

|                   |                                                                      |
|-------------------|----------------------------------------------------------------------|
| Shell Style/Model | FVS*: Straight plug with cable crimping, coaxial, threaded coupling  |
| Keying            | Circular, male                                                       |
| Housing Material  | Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces |
| Weight            | 5.17 g                                                               |

### Performance

|               |                          |
|---------------|--------------------------|
| Configuration | 00.250 : 1 Coax (50 Ohm) |
| Insulator     | T: PTFE                  |
| Rated Current | 4 Amps                   |

### Specifications

|                                      |
|--------------------------------------|
| Contact Type: Coaxial 50 Ohm (Crimp) |
| Contact Retention: 18 N              |
| Contact Dia.: 0.7 mm (0.028in)       |
| Bucket Dia.: 0.6 mm (0.024in)        |
| Test voltage: 2.1 kV (rms)           |
| R (max): 6.1 mOhm                    |
| Vtest: 2100 V (AC), 3000 V (DC)      |
| :                                    |
| Impedance: 50 Ohm                    |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


VSWR:  $1.09 + 0.11 \cdot f/\text{GHz}$

Others

- Endurance (Shell): 5000 mating cycles
- F ret (min): 100 N
- Salt Spray Corrosion: >144 hr

DRAWINGS

Draws



Dimensions

|     | A    | L    | M    |
|-----|------|------|------|
| mm. | 9    | 31   | 26.4 |
| in. | 0.35 | 1.22 | 1.04 |

RECOMMENDED BY LEMO

Tools

- Crimp Tool: [DPE.99.123.8K](#)
- Die Tool: [DPN.99.123.8K](#)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## Cables

|                     |           |       |                                                                                      |
|---------------------|-----------|-------|--------------------------------------------------------------------------------------|
| CCN.50.051.1529NMC  |           |       |                                                                                      |
| 017 420             | PVC       | Black |    |
| 017 450             | COPOLYMER | Black |    |
| 018 700             | PTFE      | White |    |
| 018 800             | PTFE      | White |                                                                                      |
| 031 600             | PTFE      | Brown |                                                                                      |
| 178 190             | PTFE      | Brown |                                                                                      |
| 196 270             | PTFE      | White |                                                                                      |
| CCX.50.030.083.180B |           | White |                                                                                      |
| CCX.50.RG0.58AU14B  | FEP       | White |                                                                                      |
| CCX.50.RG1.74-U25N  | PVC       | Black |                                                                                      |
| CCX.50.RG1.74AU28N  | PVC       | Black |                                                                                      |
| CCX.50.RG1.74AU28N  | PVC       | Black |    |
| CCX.50.RG1.74U25N   | PVC       | Black |                                                                                      |
| CCX.50.RG1.78BU18M  | FEP       | Brown |                                                                                      |
| CCX.50.RG1.78BU18M  | PTFE      | Brown |                                                                                      |
| CCX.50.RG1.88AU24B  | TFE       | White |                                                                                      |
| CCX.50.RG1.88AU26B  | PFA       | White |                                                                                      |
| CCX.50.RG1.88AU26B  | PTFE      | White |                                                                                      |
| CCX.50.RG1.96AU19B  | PTFE      | White |                                                                                      |
| CCX.50.RG1.96AU20B  | PFA       | White |                                                                                      |
| CCX.50.RG3.16BU26M  | FEP       | Brown |                                                                                      |
| CCX.50.RG3.16U28M   | PTFE      | Brown |                                                                                      |
| CCX.75.RG1.79BU26M  | FEP       | Brown |                                                                                      |
| CCX.75.RG1.87AU26B  | PFA       | White |                                                                                      |
| CCX.75.RG1.87AU27B  | PTFE      | White |  |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.