



## **SUMMARY**

#### # Wires



Image is for illustrative purpose only

Series 0B

Termination type No contacts / Accessory

IP rating (

AWG wire size 0.00 - 0.00

Cable Ø 4.50 - 5.20 mm

**Status** active

### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

### **Mechanics**

Shell Style/Model GMA\*: Bend relief Black

**Keying** No keying

Housing Material Thermoplastic polyurethane elastomer(Desmopan 786)

Variant N: Black

Weight .42 g

### **Performance**

Configuration

Insulator

**Rated Current** 


### **Others**

Temp (min / max):  $-40^{\circ}$ C /  $+80^{\circ}$ C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## **DRAWINGS**

### **Draws**



No keying

### **Dimensions**

	А	L
mm.	4.5	24
in.	0.18	0.94

# **RECOMMENDED BY LEMO**

### **Tools**

### **Cables**

420 222		
120 222		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.