

Piezo Indicators

Catalog Number	Tone	Oscillating Frequency (kHz ± 0.5)	dB (Min) @ 12V @ 30cm	Operating Voltage (VDC)	D x H (mm)	Figure	Mounting & Features	Pitch
PK-27N25W	C	2.5	90	3 ~ 28	30 x 16	2	Flange Mount (39 c/c) - 2 wire	
PK-27N26W	C	2.5	90	3 ~ 28	30 x 10	2	Flange Mount (39 c/c) - 2 wire	
PK-20A25W	C	2.5	95	3 ~ 24	23 x 18	2	Flange Mount (29 c/c) - 2 wire	
PK-27A25W	C	2.5	95	3 ~ 24	30 x 16	2	Flange Mount (39 c/c) - 2 wire	
PK-35N29W	C	2.9	90	3 ~ 28	42 x 16	2	Flange Mount (50 c/c) - 2 wire	
PK-35A29W	C	2.9	95	3 ~ 24	42 x 16	2	Flange Mount (50 c/c) - 2 wire	
PK-21N30W	C	3.0	80	1.5 ~ 30	24 x 9.5	2	Flange Mount (29 c/c) - 2 wire	
PK-21A29W	C	3.0	85	3 ~ 24	24 x 13.5	2	Flange Mount (28.4 c/c) - 2 wire	
PK-27N35W	C	3.5	90	3 ~ 28	30 x 16	2	Flange Mount (39 c/c) - 2 wire	
PK-27N36W	C	3.5	90	3 ~ 28	30 x 10	2	Flange Mount (39 c/c) - 2 wire	
PK-27A35W	C	3.5	95	3 ~ 24	30 x 16	2	Flange Mount (39 c/c) - 2 wire	
PK-20N38W	C	3.8	85	3 ~ 28	23 x 18	2	Flange Mount (29 c/c) - 2 wire	
PK-20A38W	C	3.8	95	3 ~ 24	23 x 18	2	Flange Mount (29 c/c) - 2 wire	
PK-27N35EP	C	3.5	90	3 ~ 28	See Figure	8	Panel Mount - Tamper Proof	
PK-27N35ER	C	3.5	90	3 ~ 28	See Figure	8	Panel Mount - Tamper Proof	
PK-27A35EP	C	3.5	95	3 ~ 24	See Figure	8	Panel Mount - Tamper Proof	
PK-27A35ER	C	3.5	95	3 ~ 24	See Figure	8	Panel Mount - Tamper Proof	
PK-20A35EW	C	3.5	95	3 ~ 24	See Figure	7	Panel or Flange Mount - 2 wire	
PK-27N25PS	C	2.5	90	3 ~ 28	30 x 16	1	P.C. Board - 2 pin	(15 mm c/c)
PK-27N26PS	C	2.5	90	3 ~ 28	30 x 10	1	P.C. Board - 2 pin	(15 mm c/c)
PK-20A25P	C	2.5	95	3 ~ 24	23 x 18	1	P.C. Board - 2 pin	(15 mm c/c)
MCP320B2	C	2.5	95	3 ~ 20	23 x 18	1	P.C. Board - 2 pin	(15 mm c/c)
PK-27A25PS	C	2.5	95	3 ~ 24	30 x 16	1	P.C. Board - 2 pin	(15 mm c/c)
MAS800	C	2.8	103 @ 2 ft	9 ~ 12	See Figure	9A	P.C. Board - 2 pin - Sealed Back	(15 mm c/c)
MAS800S	C	2.8	103 @ 2 ft	9 ~ 12	See Figure	9A	P.C. Board - 2 pin - Sealed	(15 mm c/c)
MAS806	C	2.8	103 @ 14V @ 2ft	5 ~ 14	See Figure	9A	P.C. Board - 2 pin - Sealed Back	(15 mm c/c)
MAS806S	C	2.8	103 @ 14V @ 2ft	5 ~ 14	See Figure	9A	P.C. Board - 2 pin - Sealed	(15 mm c/c)
MAS803	C	2.8	105 @ 7V @ 10cm	1.5 ~ 7	See Figure	9A	P.C. Board - 2 pin - Sealed Back	(15 mm c/c)
MAS803S	C	2.8	105 @ 7V @ 10cm	1.5 ~ 7	See Figure	9A	P.C. Board - 2 pin - Sealed	(15 mm c/c)
PK-21N30P	C	3.0	80	1.5 ~ 30	24 x 9.5	1	P.C. Board - 2 pin	(15 mm c/c)
PK-21N31P	C	3.0	80	1.5 ~ 30	24 x 14	1	P.C. Board - 2 pin - Sealed Back	(15 mm c/c)
PK-21A29P	C	3.0	85	3 ~ 24	24 x 14	1	P.C. Board - 2 pin	(15 mm c/c)
PK-21A31P	C	3.0	85	3 ~ 24	24 x 14	1	P.C. Board - 2 pin - Sealed Back	(15 mm c/c)
MCP320	C	3.1	74 @ 20V	3 ~ 20	24 x 17.5	1A	P.C. Board - 2 pin - Sealed	(15 mm c/c)
PK-27N35PS	C	3.5	90	3 ~ 28	30 x 16	1	P.C. Board - 2 pin	(15 mm c/c)
PK-27N36PS	C	3.5	90	3 ~ 28	30 x 10	1	P.C. Board - 2 pin	(15 mm c/c)
PK-27A35PS	C	3.5	95	3 ~ 24	30 x 16	1	P.C. Board - 2 pin	(15 mm c/c)
PK-20N38P	C	3.8	85	3 ~ 28	23 x 18	1	P.C. Board - 2 pin	(15 mm c/c)
PK-20A38P	C	3.8	95	3 ~ 24	23 x 18	1	P.C. Board - 2 pin	(15 mm c/c)
PK-12N40P	C	4.1	83 @ 10cm	3 ~ 15	13.8 x 7.5	1	P.C. Board - 2 pin	(7.6 mm c/c)
PK-12N40PE	C	4.1	83 @ 10cm	3 ~ 15	13.8 x 7.5	1A	P.C. Board - 2 pin - Sealed	(7.6 mm c/c)
PFD-35N29W	C/FP	2.9	90	3 ~ 28	42 x 16	2	Flange Mount (50 c/c) - 3 wire	
PFD-35A29W	C/FP	2.9	95	3 ~ 24	42 x 16	2	Flange Mount (50 c/c) - 3 wire	
PFD-21N30W	C/FP	3.0	80	3 ~ 30	24 x 9.5	2	Flange Mount (29 c/c) - 3 wire	
PFD-21A29W	C/FP	3.0	85	3 ~ 24	24 x 13.5	2	Flange Mount (28.4 c/c) - 3 wire	
PFD-27N36W	C/FP	3.5	90	3 ~ 28	30 x 10	2	Flange Mount (39 c/c) - 3 wire	
PFD-27N35W	C/FP	3.5	90	3 ~ 28	30 x 16	2	Flange Mount (39 c/c) - 3 wire	
PFD-27A35W	C/FP	3.5	95	3 ~ 24	30 x 16	2	Flange Mount (39 c/c) - 3 wire	
PFD-27N35EP	C/FP	3.5	90	3 ~ 28	See Figure	8	Panel Mount - Tamper Proof	
PFD-27N35ER	C/FP	3.5	90	3 ~ 28	See Figure	8	Panel Mount - Tamper Proof	
PFD-27A35EP	C/FP	3.5	95	3 ~ 24	See Figure	8	Panel Mount - Tamper Proof	
PFD-27A35ER	C/FP	3.5	95	3 ~ 24	See Figure	8	Panel Mount - Tamper Proof	
PFD-20A35EW	C/FP	3.5	95	3 ~ 24	See Figure	7	Panel or Flange Mount - 3 wire	
PFD-21N30P	C/FP	3.0	80	3 ~ 30	24 x 9.5	1	P.C. Board - 3 pin	P2 (7.5mm), P3 (7.5mm)
PFD-27N35P	C/FP	3.5	90	3 ~ 28	30 x 16	1	P.C. Board - 3 pin	P2 (7mm), P3 (11mm)
PFD-27N36P	C/FP	3.5	90	3 ~ 28	30 x 10	1	P.C. Board - 3 pin	P2 (7mm), P3 (11mm)
PFD-27A35P	C/FP	3.5	95	3 ~ 24	30 x 16	1	P.C. Board - 3 pin	P2 (7mm), P3 (11mm)
PLD-35N29W	C/SP	2.9	90	3 ~ 28	42 x 16	2	Flange Mount (50 c/c) - 3 wire	
PLD-35A29W	C/SP	2.9	95	3 ~ 24	42 x 16	2	Flange Mount (50 c/c) - 3 wire	
PLD-21N30W	C/SP	3.0	80	3 ~ 30	24 x 9.5	2	Flange Mount (29 c/c) - 3 wire	
PLD-21A29W	C/SP	3.0	85	3 ~ 24	24 x 13.5	2	Flange Mount (28.4 c/c) - 3 wire	
PLD-27N36W	C/SP	3.5	90	3 ~ 28	30 x 10	2	Flange Mount (39 c/c) - 3 wire	
PLD-27N35W	C/SP	3.5	90	3 ~ 28	30 x 16	2	Flange Mount (39 c/c) - 3 wire	
PLD-27A35W	C/SP	3.5	95	3 ~ 24	30 x 16	2	Flange Mount (39 c/c) - 3 wire	
PLD-27N35EP	C/SP	3.5	90	3 ~ 28	See Figure	8	Panel Mount - Tamper Proof	
PLD-27N35ER	C/SP	3.5	90	3 ~ 28	See Figure	8	Panel Mount - Tamper Proof	
PLD-27A35EP	C/SP	3.5	95	3 ~ 24	See Figure	8	Panel Mount - Tamper Proof	

'C' = Constant, 'FP' = Fast Pulse, 'SP' = Slow Pulse