

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ SNAP-ACTION SWITCHES

Snap-action switches

SERIES 1005 - MINIATURE SNAP-ACTION SWITCHES - TO 21 (8) A 250 V AC

[◀ Show previous product](#)[Show next product ▶](#)

1006.1201

Drawing

Accessories

Similar to original
product[→ Print data sheet](#)

Product number	1006.1201
Switching function	Changeover switch (SPDT momentary)
Number of poles	1-pole
connections	Quick-connect terminal, 6.3
Mechanical life endurance	5E6
Rating IEC	10 (4) A 400 V AC 1E4 6 (2.5) A 400 V AC 5E4
Rating North America	10 A 125 - 250 V AC 1/4 HP
Design	DIN 41635 A
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Ambient temperature	-40 °C ... +100 °C
Flammability	UL 94 (housing: V-0, actuator: V-2)
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, galvanized steel, L 11, lever 20.6 long with roller diameter 5 of PA yellow
Housing description	Duroplast type 182
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	< 3 mm
Operating force	1.5 - 2.5 N
Bounce time	< 10 ms
Difference travel max.	0.3 mm
Free position (FP) max.	22.1 mm
Operating position (OP)	20.8 ±0.5 mm
Permissible total travel position	19.5 mm
Approval marks	CSA / UL / ENEC 05
Shop / Stock version	