

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ SNAP-ACTION SWITCHES

Snap-action switches

SERIES 1055 - SUBSUBMINIATURE SNAP-ACTION SWITCHES IP 67 - TO 4 A 12 V
OR 2 A 24 V DC[◀ Show previous product](#)[Show next product ▶](#)

1055.8155

Drawing

Similar to original
product[→ Print data sheet](#)

Product number	1055.8155
Miscellaneous	pin right 2.5 long
Switching function	Changeover switch (SPDT momentary)
Number of poles	1-pole
connections	PCB terminal, right
Mechanical life endurance	5E5
Rating IEC	2 A 24 V DC (ohmsche Last) 4 A 12 V DC (ohmsche Last)
Contact resistance (new condition)	< 50 mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Protection type	Connection IP 00
Ambient temperature	-40 °C ... +85 °C
Flammability	UL 94 HB
Actuators and additional actuators	POM, stainless steel spring steel, L21, lever simulated roller, silicone rubber
Housing description	PBTP
Connection surface	external connection tinned
Contact material	Au
Operating force	≥ 2.6 N
Difference travel max.	0.8 mm
Free position (FP) max.	14.7 mm
Operating position (OP)	12.4 ±0.65 mm
Permissible total travel position	10.3 mm