

[General information](#)[Rocker switches](#)[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[Sensors](#)[Catalog request / download](#)[Login](#)[www.marquardt.com](#)[Download](#)[Sales international](#)[Partner access](#)[Previous](#)

Product 34 of 43

[Next](#)**Technical data**

Product number	1552.3111	
Actuator color / printing		
Inrush current (capacitive)	100 A	
Switching function	ON / OFF switch (DPST)	
Number of poles	2-pole	
connections	Quick-connect terminal, 6.3	
Mechanical life endurance	5E4	
Rating IEC	10 (4) A 250 V AC 5E4 16 (4) A 250 V AC 1E4	
Rating North America	16 A 125 V AC 1 HP 16 A 250 V AC 2 HP	
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm	
Insulation resistance (new condition)	> 100 (500 V DC) MOhm	
Voltage strength at 250 V	function insulation / basic insulation	1 500 V
	reinforced insulation	3 000 V
	small contact distance	500 V
Proof tracking	250 PTI	
Insulation spacing	acc. to EN 61058 for reinforced or double insulation	
Protection type	Connection	IP 40
Temperature	Actuation side min.	-20 °C
	Actuation side max.	55 °C
	Connection side min.	-20 °C
	Connection side max.	100 °C
Flammability	UL 94 V-2	
Heat and fire resistance	850 °C (category 3)	
Actuators and additional actuators	PA, black	
Housing description	PA, black	
Contact material	Ag	
Contact distance	? 3 mm	
Plug force of the terminals	? 80 N	
Approval marks	CSA / ENEC 05 / UL	
Suitable for appliances of protection class	II	

[Back](#)