

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ PUSHBUTTON SWITCHES

Pushbutton switches

SERIES 1660 - SINGLE AND DOUBLE-POLE PUSHBUTTON SWITCHES - TO 16 (4)
A 250 V AC[◀ Show previous product](#)[Show next product ▶](#)

1660.3202

[Drawing](#)[Accessories](#)Similar to original
product[→ Print data sheet](#)

Product number	1660.3202
Actuator color / printing	
Miscellaneous	external lamp connection
Switching function	ON / OFF switch (DPST)
Number of poles	2-pole
connections	Quick-connect terminal, 6.3 / 2 x 4.8
Mechanical life endurance	5E4
Rating IEC	16 (4) A 250 V AC 1E4
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +85 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PC, transparent green
Housing description	PA, PA glass fiber-reinforced, black
Connection surface	external connection Cu
Contact material	Ag
Contact distance	≥ 3 mm
Lighting	230 V
Plug force of the terminals	≤ 80 N
Approval marks	ENEC 05
Suitable for appliances of protection class	I