

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ PUSHBUTTON SWITCHES

Pushbutton switches

SERIES 1660 - SINGLE AND DOUBLE-POLE PUSHBUTTON SWITCHES - TO 16 (4)
A 250 V AC[◀ Show previous product](#)[Show next product ▶](#)

1661.0220

[Drawing](#)[Accessories](#)Similar to original
product[→ Print data sheet](#)

Product number	1661.0220
Actuator color / printing	
Switching function	ON / OFF switch (DPST)
Number of poles	2-pole
connections	Quick-connect terminal, 6.3
Mechanical life endurance	5E4
Rating IEC	16 (4) A 250 V AC
Rating North America	12 A 125 V AC 1/6 HP 12 A 250 V AC 1/2 HP
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +85 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, black
Housing description	PA, PA glass fiber-reinforced, black
Connection surface	external connection Cu
Contact material	Ag
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 80 N
Approval marks	CSA / UL / ENEC 05
Suitable for appliances of protection class	I