

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ PUSHBUTTON SWITCHES

Pushbutton switches

SERIES 1670 - SINGLE AND DOUBLE-POLE PUSHBUTTON SWITCHES - TO 16 (4)
A 250 V AC

◀ Show previous product

Show next product ▶

1670.5202

Drawing

Similar to original
product

→ Print data sheet

Product number

1670.5202

Actuator color / printing



Switching function

ON / OFF switch (DPST)

Number of poles

2-pole

connections

Quick-connect terminal, 6.3

Mechanical life endurance

5E4

Rating IEC

16 (4) A 250 V AC 1E4

Contact resistance (new
condition)

< 100 (1 A 12 V DC) mOhm

Insulation resistance (new
condition)

> 100 (500 V DC) MOhm

Proof tracking

250 PTI

Protection type

Connection IP 54

Ambient temperature

-20 °C ... +85 °C

Ambient temperature

-20 °C ... +55 °C

Flammability

UL 94 V-2

Glow wire test temperature

850 °C

Actuators and additional
actuators

PC, green

Housing description

PA, black

Connection surface

external connection Cu

Contact material

Ag

Contact distance

≥ 3 mm

Lighting

230 V

Plug force of the terminals

≤ 80 N

Operating force

approx. 8 N

Approval marks

ENEC 05

Suitable for appliances of
protection class

I

Shop / Stock version

