

## PRODUCTS

[Rocker switches](#)**[Pushbutton switches](#)**[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[ECO switches](#)[Sensors](#)[Systems and modules](#)[Accessories](#)[General information](#)[Catalog request /  
download](#)PRODUCTS ▶ [PUSHBUTTON SWITCHES](#)


## Pushbutton switches

### SERIES 1670 - SINGLE AND DOUBLE-POLE PUSHBUTTON SWITCHES - TO 16 (4) A 250 V AC

[Show next product ▶](#)

1675.5315

[Drawing](#)[Accessories](#)Similar to original  
product[→ Print data sheet](#)

Product number	1675.5315
Actuator color / printing	
Miscellaneous	external lamp connections
Switching function	Normally open contact (SPNO)
Number of poles	1-pole
connections	Quick-connect terminal, 6.3 / 2 x 4.8
Mechanical life endurance	5E4
Rating IEC	16 (4) A 250 V AC 1E4
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 54
Ambient temperature	-20 °C ... +85 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PC, white
Housing description	PA, black
Connection surface	external connection Cu
Contact material	Ag
Contact distance	≥ 3 mm
Lighting	230 V
Plug force of the terminals	≤ 80 N
Operating force	approx. 8 N
Approval marks	ENEC 05
Suitable for appliances of protection class	I