

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ TOGGLE SWITCHES

Toggle switches

SERIES 1810 - SINGLE AND DOUBLE-POLE TOGGLE SWITCHES - TO 10 (4) A
250 V AC[◀ Show previous product](#)[Show next product ▶](#)

1818.1102

Drawing

Accessories

Similar to original
product[→ Print data sheet](#)

Product number	1818.1102
Actuator color / printing	
Switching function	Changeover switch with OFF position in the center (SPDT - Center OFF)
Number of poles	1-pole
connections	Quick-connect terminal, 4.8
Mechanical life endurance	5E4
Rating IEC	6 (2) A 250 V AC 1E4
Rating North America	6 A 125 - 250 V AC 1/8 HP
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +100 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, black
Housing description	PA, black
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	< 3 mm
Plug force of the terminals	≤ 80 N
Approval marks	CSA / UL / ENEC 05
Suitable for appliances of protection class	I
Shop / Stock version	