

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ ROCKER SWITCHES

Rocker switches

SERIES 1830 - SINGLE AND DOUBLE-POLE ROCKER SWITCHES - TO 20 (4) A 250 V AC

◀ Show previous product

Show next product ▶

1834.6103

Drawing

Similar to original
product

→ Print data sheet

Product number

1834.6103

Actuator color / printing



Miscellaneous

lower lying flange

Switching function

Changeover switch (DPDT)

Number of poles

2-pole

connections

Quick-connect terminal, 4.8

Mechanical life endurance

10E4

Rating IEC

10 (4) A 250 V AC 1E4
6 (4) A 250 V AC 5E4

Rating North America

6 A 125 V AC 1/4 HP
6 A 250 V AC 1/2 HPContact resistance (new
condition)

< 100 (1 A 12 V DC) mOhm

Insulation resistance (new
condition)

> 100 (500 V DC) MOhm

Proof tracking

250 PTI

Protection type

Connection IP 40

Ambient temperature

-20 °C ... +105 °C

Ambient temperature

-20 °C ... +55 °C

Flammability

UL 94 V-2

Glow wire test temperature

850 °C

Actuators and additional
actuators

PA, black

Housing description

PA, black

Connection surface

external connection silver plated

Contact material

Ag

Contact distance

≥ 3 mm

Plug force of the terminals

≤ 80 N

Approval marks

CSA / UL / ENEC 05

Suitable for appliances of
protection class

I