

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ ROCKER SWITCHES

Rocker switches

SERIES 1830 - SINGLE AND DOUBLE-POLE ROCKER SWITCHES - TO 20 (4) A 250 V AC

[◀ Show previous product](#)[Show next product ▶](#)

1839.7304

Drawing

Similar to original
product[→ Print data sheet](#)

Product number

1839.7304

Actuator color / printing

I
O
R

Miscellaneous

lower lying flange / dust protection inlay / momentary function one side

Switching function

Changeover switch with OFF position in the center (DPDT - Center OFF)

Number of poles

2-pole

connections

PCB terminal

Mechanical life endurance

5E4

Rating IEC

6 (4) A 250 V AC 1E4

Rating North America

6 A 125 - 250 V AC 1/8 HP

Contact resistance (new
condition)

< 100 (1 A 12 V DC) mOhm

Insulation resistance (new
condition)

> 100 (500 V DC) MOhm

Proof tracking

250 PTI

Protection type

Connection IP 40

Ambient temperature

-20 °C ... +105 °C

Ambient temperature

-20 °C ... +55 °C

Flammability

UL 94 V-2

Glow wire test temperature

850 °C

Actuators and additional
actuators

PA, black

Housing description

PA, black

Connection surface

external connection silver plated

Contact material

Ag

Contact distance

≥ 3 mm

Plug force of the terminals

≤ 80 N

Approval marks

CSA / UL / ENEC 05

Suitable for appliances of
protection class

I