

PRODUCTS**Rocker switches**[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[ECO switches](#)[Sensors](#)[Systems and modules](#)[Accessories](#)[General information](#)[Catalog request /
download](#)PRODUCTS ▶ [ROCKER SWITCHES](#)**Rocker switches****SERIES 1855 - MINIATURE DOUBLE-POLE ROCKER SWITCHES - TO 4 (1) A 250 V AC**[◀ Show previous product](#)[Show next product ▶](#)

1855.1104

[Drawing](#)[Accessories](#)Similar to original
product[→ Print data sheet](#)

Product number	1855.1104
Actuator color / printing	
Switching function	ON / OFF switch (DPST)
Number of poles	2-pole
connections	Quick-connect terminal, 4.8
Mechanical life endurance	5E4
Rating IEC	4 (1) A 250 V AC 1E4
Rating North America	4 A 250 V AC 1/10 HP
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +85 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, transparent orange
Housing description	PA, black
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	≥ 3 mm
Lighting	230 V
Plug force of the terminals	≤ 80 N
Approval marks	CSA / UL / ENEC 05
Suitable for appliances of protection class	I
Shop / Stock version	