

PRODUCTS

Rocker switches

[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[ECO switches](#)[Sensors](#)[Systems and modules](#)[Accessories](#)[General information](#)[Catalog request /
download](#)PRODUCTS ▶ [ROCKER SWITCHES](#)

Rocker switches

SERIES 1881 - SINGLE-POLE ROUND ROCKER SWITCHES - TO 12 (4) A 250 V AC

[Show next product ▶](#)

1881.1103

[Drawing](#)Similar to original
product[→ Print data sheet](#)

Product number

1881.1103

Actuator color / printing



Inrush current (capacitive)

70 A

Switching function

ON / OFF switch (SPST)

Number of poles

1-pole

connections

Quick-connect terminal, 4.8

Mechanical life endurance

10E4

Rating IEC

12 (4) A 250 V AC 1E4
8 (8) A 250 V AC 5E4

Rating North America

15 A 125 V AC 3/4 HP
15 A 250 V AC 1 1/2 HPContact resistance (new
condition)

< 100 (1 A 12 V DC) mOhm

Insulation resistance (new
condition)

> 100 (500 V DC) MOhm

Proof tracking

250 PTI

Protection type

Connection IP 40
Actuator IP 40

Ambient temperature

-20 °C ... +100 °C

Ambient temperature

-20 °C ... +55 °C

Flammability

UL 94 V-2

Glow wire test temperature

850 °C

Actuators and additional
actuators

PA, black

Housing description

PA, black

Connection surface

external connection silver plated

Contact material

Ag

Contact distance

≥ 3 mm

Plug force of the terminals

≤ 80 N

Operating force

3 N

Approval marks

cULus / ENEC 05

Suitable for appliances of
protection class

I

Shop / Stock version

