

PRODUCTS

Rocker switches

[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[ECO switches](#)[Sensors](#)[Systems and modules](#)[Accessories](#)[General information](#)[Catalog request /
download](#)PRODUCTS ▶ [ROCKER SWITCHES](#)

Rocker switches

SERIES 1900 - SMALLEST SINGLE-POLE ROCKER SWITCHES - TO 6 (2) A 250 V AC

[◀ Show previous product](#)
[Show next product ▶](#)

1911.1104

[Drawing](#)


Similar to original
product

[→ Print data sheet](#)

Product number	1911.1104
Actuator color / printing	
Switching function	ON / OFF switch (SPST)
Number of poles	1-pole
connections	Quick-connect terminal, 4.8
Mechanical life endurance	75E3
Rating IEC	6 (2) A 250 V AC 4 (1) A 250 V AC 5E4
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +85 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, black
Housing description	PA, black
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 80 N
Operating force	2 - 5 N
Approval marks	cULus / ENEC 05
Suitable for appliances of protection class	I