

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ ROCKER SWITCHES

Rocker switches

SERIES 1930 - DOUBLE-POLE ROCKER SWITCHES IP 65 - TO 20 (4) A 250 V AC

◀ Show previous product

Show next product ▶

1932.3112

Drawing

Similar to original
product

→ Print data sheet

Product number	1932.3112
Actuator color / printing	
Inrush current (capacitive)	120 A
Switching function	ON / OFF switch (DPST)
Number of poles	2-pole
connections	Quick-connect terminal, 6.3
Mechanical life endurance	5E4
Rating IEC	16 (16) A 127 V AC 16.1 (8) A 250 V AC 5E4 20 (10) A 250 V AC
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-30 °C ... +80 °C
Ambient temperature	-30 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PC, TPU, black
Housing description	PA, black
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 80 N
Operating force	3 - 8 N
Approval marks	ENEC 15 / cULus
Suitable for appliances of protection class	I
Shop / Stock version	