

[General information](#)[Rocker switches](#)[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[Sensors](#)[Catalog request / download](#)[Login](#)[www.marquardt.com](#)[Download](#)[Sales international](#)[Partner access](#)[Previous](#)

Product 27 of 35

[Next](#)**Technical data**

Product number	1934.3113	
Actuator color / printing		
Switching function	Changeover switch (DPDT)	
Number of poles	2-pole	
connections	Quick-connect terminal, 6.3	
Mechanical life endurance	5E4	
Rating IEC	10 (8) A 250 V AC 5E4	
Rating North America	12 A 250 V AC 1 HP 12 A 125 V AC 1/2 HP	
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm	
Insulation resistance (new condition)	> 100 (500 V DC) MOhm	
Voltage strength at 250 V	function insulation / basic insulation	1 500 V
	reinforced insulation	3 000 V
	small contact distance	500 V
Proof tracking	250 PTI	
Insulation spacing	acc. to EN 61058 for reinforced or double insulation	
Protection type	Connection	IP 65
Temperature	Actuation side min.	-30 °C
	Actuation side max.	55 °C
	Connection side min.	-30 °C
	Connection side max.	105 °C
Flammability	UL 94 V-2	
Heat and fire resistance	850 °C (category 3)	
Actuators and additional actuators	PC, red, TPE, black	
Housing description	PA, black	
Connection surface	external connection	silver plated
Contact material	Ag	
Contact distance	? 3 mm	
Plug force of the terminals	? 80 N	
Operating force	3 - 8 N	
Approval marks	cCSAus / ENEC 05	
Suitable for appliances of protection class	II	

[Back](#)