

PRODUCTS**Rocker switches**[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[ECO switches](#)[Sensors](#)[Systems and modules](#)[Accessories](#)[General information](#)[Catalog request /
download](#)[PRODUCTS](#) ▶ [ROCKER SWITCHES](#)**Rocker switches****SERIES 1930 - DOUBLE-POLE ROCKER SWITCHES IP 65 - TO 20 (4) A 250 V AC**[◀ Show previous product](#)[Show next product ▶](#)

1935.3114

[Drawing](#)Similar to original
product[→ Print data sheet](#)

Product number	1935.3114
Actuator color / printing	
Inrush current (capacitive)	120 A
Switching function	ON / OFF switch (DPST)
Number of poles	2-pole
connections	Quick-connect terminal, 6.3
Mechanical life endurance	5E4
Rating IEC	20 (4) A 250 V AC 1E4 10 (8) A 250 V AC 5E4
Rating North America	16 A 125 V AC 3/4 HP 16 A 250 V AC 1 HP
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-30 °C ... +105 °C
Ambient temperature	-30 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PC, transparent orange, TPU, black
Housing description	black, PA
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	≥ 3 mm
Lighting	250 V
Plug force of the terminals	≤ 80 N
Operating force	3 - 8 N
Approval marks	cCSAus / ENEC 05
Suitable for appliances of protection class	I
Shop / Stock version	