

Proheat® 1300 Variair® Temperature Heat Gun & Kit



CALL US: 1.800.558.9413

 [Ask A Question](#)

 [Request A Catalog](#)

 [View/Print Catalog](#)

 [Receive Master Updates](#)

 [Where To Buy](#)

SHARE THIS PAGE



Features

Videos

Support Materials

Attachments/Accessories

Heat Activated Materials

Compact, lightweight, easy-to-use dial-in airflow and variable temperature heat gun

≡ [Models](#)
≡ [Specifications](#)

- Compact, light weight, easy-to-use design
- Variable temperature 130°F to 1000°F (50°C to 540°C)
- Variable airflow 4 to 16 CFM
- Special electronic closed loop temperature control system maintains constant temperature when varying airflow or using specialty attachments
- Kit includes Proheat Variair Temperature Heat Gun, attachments 35016, 35017, 35292, 35293, 35294, and 35351 storage carrying case
- Accessories also available separately
- Use to heat temperature sensitive materials including specialty connectors, solder preforms, shrink tubing and more

Available Models

MODEL NO.	DESCRIPTION
PH-1300	Proheat Variair Heat Gun, Variable temp. 130°F (50°C) to 1000°F (540°C), Variable airflow 4 to 16 CFM, 120V, 60 Hz, 11A, 1300W Max
PH-1300K	Proheat Variair Heat Gun Kit includes PH-1300 Variair Heat Gun, 3" spreader attachment, shrink tubing attachment, special connector, 9/16" reducer, and 5/16" reducer packed in a rugged storage & carrying case
PH-2300 - Coming Soon	Proheat Variair Heat Gun, Variable temp. 130°F (50°C) to 1000°F (540°C), Variable airflow 4 to 16 CFM, 230V*, 50/60 Hz, 6.2A, 1426W Max
PH-2300K - Coming Soon	Proheat Variair Heat Gun Kit includes PH-2300 Variair Heat Gun, 3" spreader attachment, shrink tubing attachment, special connector, 9/16" reducer, and 5/16" reducer packed in a rugged storage & carrying case

Specifications

Temperature: Variable 130°F - 1000°F
(50°F - 540°C)

Avg. Air Volume: 4-16 CFM/113-453 l/min

Avg. Air Velocity: 737-4000 FPM/
213-1219m/min

Motor: Permanent Magnet

Dimensions: 8.2" L x 3.0" W x 7.3" H

Nozzle Opening: 1.3" O.D.

Cordset: 6 ft., 3-wire grounded

Net Weight - Single Unit: 1.6 lbs.,
Kit: 4.5 lbs.

Shipping Weight - Single Unit: 2 lbs.,
Kit: 7 lbs.



