



- Features :


- 2:1 wide input range
- 4:1 wide input range(optional)
- 1000VDC I/O isolation
- 3000VDC I/O isolation (option)
- Input Pi network filter
- Protections: Short circuit/ Over load
- Free air convection
- Five-sided shield metal case
- High reliability / Low cost
- 100% burn-in test
- 1 year warranty

SPECIFICATION

ORDER NO.		DLW05A-05	DLW05B-05	DLW05C-05	DLW05A-12	DLW05B-12	DLW05C-12	DLW05A-15	DLW05B-15	DLW05C-15	
OUTPUT	DC VOLTAGE	±5V			±12V			±15V			
	CURRENT RANGE	±50 ~ ±500mA			±20.8 ~ ±208mA			±16.7 ~ ±167mA			
	RATED POWER	5W									
	RIPPLE & NOISE (max.) Note.2	50mVp-p			60mVp-p			60mVp-p			
	LINE REGULATION Note.3	±0.2%									
	LOAD REGULATION Note.4	±0.5%									
	VOLTAGE ACCURACY	±2.0%									
	SWITCHING FREQUENCY	50KHz min.									
INPUT	VOLTAGE RANGE	A: 9 ~ 18VDC B: 18~36VDC C: 36~72VDC									
	EFFICIENCY (Typ.)	75%	77%	77%	80%	82%	83%	81%	83%	85%	
	DC CURRENT	Full load	A: 556mA B: 270mA C: 135mA								
		No load	A: 33mA B: 16mA C: 10mA								
	FILTER	Pi network									
PROTECTION (Note. 5)	OVER LOAD	160~250% rated output power									
		Protection type : Hiccup mode, recovers automatically after fault condition is removed									
	SHORT CIRCUIT	All output equipped with short circuit									
		Protection type : Hiccup mode, recovers automatically after fault condition is removed									
ENVIRONMENT	WORKING TEMP.	-25~+71℃ (Refer to output load derating curve)									
	WORKING HUMIDITY	20%~90% RH non-condensing									
	STORAGE TEMP., HUMIDITY	-25~+105℃, 10~95% RH									
	TEMP. COEFFICIENT	±0.03% / °C (0~50℃)									
	VIBRATION	10~500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes									
SAFETY & EMC	WITHSTAND VOLTAGE	I/P-O/P:1KVDC									
	ISOLATION RESISTANCE	I/P-O/P: 100M Ohms / 500VDC									
OTHERS	MTBF	800khrs min. MIL-HDBK-217F(25℃)									
	DIMENSION	50.8*25.4*11.27mm or 2.0"*1.0"*0.44" inch (L*W*H)									
	WEIGHT	32g									

■ Mechanical Specification


Unit:mm(inch)



■ Pin Configuration

Pin no.	Output
	Dual
1	+Vin
2	-Vin
3	+Vout
4	COM
5	-Vout

Derating Curve



NOTE

- 1.All parameters are specified at normal input, rated load, 25°C 70% RH. Ambient.
- 2.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
- 3.Line regulation is measured from low line to high line at rated load.
- 4.Load regulation is measured from 10% to 100% rated load.
- 5.Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.