

Data Sheet

PR015xxVBHC


Page 1/5

P/N

310171xx

xx=number of poles

Illustration



see enlarged drawing at the end of the document

Product specification

- pin header, THR solderable
- centerline 5.00 mm, direction of connection vertical 0°
- fittable without loss of poles
- color black
- Tape & Reel packaging
- Connection data

RIA US V / A 300 / 15

S 250 V / 4 kV / 10 A

Data Sheet

PR015xxVBHC

Page 2/5

P/N

310171xx

xx=number of poles

Technical Data

General Data

Solder pin length	3.4 mm		
min. number of poles	2		
max. number of poles	24		
Insulating material class	CTI 400		
clearance/creepage dist.	3.7 mm		
protection category	IP 00		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	250 V	500 V	500 V
Rated test voltage	2.5 kV	4 kV	2.5 kV

Connection data

 V / A	300 / 15
	250 V / 4 kV / 10 A

Material

insulating material	PA46
flammability class	V0
contact pin material	CuZn
contact pin surface	Ni + Ag

Climatic properties

upper limit temperature	105 °C
lower limit temperature	-40 °C

General

solderability	For THR products acc. to IPC/JEDEC J-STD-020D-MSL 1 For THT products max. 260 °C / 10 s
Tolerance	ISO 2768 -mH

Data Sheet

PR015xxVBHC

Page 3/5

P/N

310171xx

xx=number of poles

Matching Part to

P/N	Product name
310071	Type 007
310261	Type 026
310771	Type 077
311071	Type 107
ASP025	ASP025
ASP145XX22-131 (on request)	kalibriert für 1,3 mm Stifte
ASP155XX22-131 (on request)	kalibriert für 1,3 mm Stifte

Data Sheet

PR015xxVBHC

Page 4/5





P/N

310171xx

xx=number of poles

Illustration

Drawing



$L = (\text{pole size} - 1) \times \text{centerline} + 4.8 [0.189]$

Data Sheet

PR015xxVBHC

Page 5/5

P/N

310171xx

xx=number of poles

PCB Layout

