

Type 360291



Type 360271



Description Type 360291

Single terminal block, solderable, horizontal wire entry, lift system, with molded housing, double solder pins


Technical Data Type 360291

UL V / A / AWG 50 / 15 / 22 - 14
CE V / A / AWG 50 / 15 / 22 - 14
 Screw torque max. 7 lbs.-in

0.05 - 1.5 mm² 16 A
 Screw torque max. 0.5 Nm

Wire diameter	single wire 0.3 - 1.6 mm
Wire strip length	5 mm / 0.197 in.
Solder pin	2 x □ 1 mm 2 x □ 0.039 in. spacing 4 mm / 0.157 in. recommended pc board hole dia. 1.5 mm / 0.059 in.
Solder pin length	3.5 mm / 0.138 in.
Colour	black

Dimensions in mm 1 mm = 0.0394 in.



Description Type 360271

Single terminal block, solderable, horizontal wire entry, lift system, with molded housing, single solder pin


Technical Data Type 360271

UL V / A / AWG 50 / 15 / 24 - 14
CE V / A / AWG 50 / 15 / 24 - 14
 Screw torque max. 7 lbs.-in

0.05 - 1.5 mm² 16 A
 Screw torque max. 0.5 Nm

Wire diameter	single wire 0.3 - 1.6 mm
Wire strip length	5 mm / 0.197 in.
Solder pin	dia. 1.2 mm / 0.047 in. recommended pc board hole dia. 1.5 mm / 0.059 in.
Solder pin length	2.9 mm / 0.114 in.
Colour	black

Dimensions in mm 1 mm = 0.0394 in.



Type 360291

with double soldering pins
 P/N 360291

Type 360271

with single soldering pin
 P/N 360271