

RTV Silicones

[One Part](#)
[Two Part](#)
[Primers](#)
[Selection Guides](#)

ALL MG PRODUCTS ▾

[Accessories](#)
[Adhesives](#)
[Brushes](#)
[Cleaners / Degreasers](#)
[Contact Cleaners](#)
[Desoldering Braid](#)
[Dusters & Circuit Coolers](#)
[EMI / RFI Shielding](#)
[Epoxyes](#)
[Flux and Flux Remover](#)
[Glass & Screen Cleaners](#)
[Lubricants](#)
[Potting & Encapsulating](#)
[Protective Coatings](#)
[Pens](#)
[Prototyping Materials](#)
[RTV Silicones](#)
[Specialized Cleaners](#)
[Swabs](#)
[Thermal Management](#)
[Thermally Conductive Adhesives](#)
[Wipes](#)

RTV Silicones by

2-Part Potting/Encapsulating Compound RTV60

[▶ STOCKED ITEM](#)
[▶ BUY NOW](#)

Primary Characteristics

- ▶ Red flowable
- ▶ **Extreme high temp.**
- ▶ Condensation cure
- ▶ Useful to 260°C (500°F)
- ▶ Thermal insulator
- ▶ Primer required

Use for:

- ▶ Aerospace applications such as potting, encapsulating, coating and cushioning

Excellent for potting and encapsulating electric motors and transformers. Also used for fabrication of rubber parts and casting molds for low-melting point metals. Recommended for aerospace applications and as a thermal insulator. Excellent retention of elastomeric properties at temperatures from -54°C to 260°C (-65°F to 500°F) continuously, and up to 316°C (600°F) for short periods of time. Cures at room temperature and has excellent adhesion qualities. A [silicone primer](#) is required. The product comes complete with catalyst DBT. [Specialized catalysts](#) are available upon request. RTV60 is a low viscosity version of [RTV88](#) and will flow into small areas.

Available Sizes

Catalog Number	Sizes Available	Description
RTV60-1P	1 pint	pail
RTV60-1G ▶ SPECIAL ORDER	1 gallon	pail
RTV60-5G ▶ SPECIAL ORDER	5 gallon	pail
RTV60 requires a primer. Visit our primer guide for details.		





Specifications

Use	Potting & Encapsulating
Special Feature	High Temperature
Cross Reference	RTV60
Uncured Properties	
Consistency	Flowable
Color	Red
Specific Gravity	1.48
Pot Life	2 hours
Cure Through Time	24 hours
Useful Temp. Range	-54°C to 260°C (-65°F to 500°F)
Cured Properties - MECHANICAL	
Hardness	57 (Shore A)
Tensile Strength	6.86 MPa (990 psi)

Quick Links

- ▶ [MSDS](#)
- ▶ [Catalyst options/MSDS](#)
- ▶ [Primer options/MSDS](#)
- ▶ [Specifications](#)
- ▶ [Available Sizes](#)
- ▶ [Handling & Safety](#)
- ▶ [Application](#)
- ▶ [Surface Preparation](#)
- ▶ [Warranty](#)

Related Products:

-  [RTV31](#)
-  [RTV88](#)
-  [RTV560](#)
-  [RTV566](#)

Find by Product Number



Resources

- [What are RTV Silicones? >](#)
- [Application Guide >](#)
- [Product Data Spreadsheet >](#)

Find by Application

- [General Purpose >](#)
- [Aerospace >](#)
- [Marine >](#)
- [High Performance Assembly >](#)
- [Electronics >](#)
- [Thermal Conductivity >](#)
- [High Temperature >](#)
- [Low Temperature >](#)



Elongation	120%
Cured Properties - ELECTRICAL	
Volume Resistivity	4.4 x 10 ¹⁴ ohm · cm
Dielectric Strength	17.7 kV/mm (450 V/mil)
Dielectric Constant	4.0 @ 1000Hz
Cured Properties - THERMAL	
Thermal Conductivity	0.31 W/m · °K
Thermal Expansion	20 x 10 ⁻⁵ cm/cm °C
	(11 x 10 ⁻⁵ in/in °F)
Other	
Viscosity (@ 25°C)	47,000 cps
Mix ratio (by weight)	100:0.5

[Return to top](#) ^