



Micro Commercial Components




Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

1SS133

High Speed
Switching Diode

DO-35



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	---	.166	---	4.2	
B	---	.079	---	2.00	
C	---	.020	---	.52	
D	1.000	---	25.40	---	

Features

- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Glass sealed envelope.
- High speed. ($t_r=1.2\text{ns}$ Typ)
- High reliability.
- Silicon epitaxial planar
- Marking : Cathode band and type number
- Moisture Sensitivity Level 1

Absolute maximum Ratings

Symbol	Rating	Rating	Unit
V_{RM}	Peak Reverse Voltage	90	V
V_R	DC Reverse Voltage	80	V
I_{FM}	Peak Forward Current	400	mA
I_o	Mean Rectifying Current	130	mA
I_{surge}	Surge Current (1s)	600	mA
P_D	Power Dissipation	300	mW
T_J	Operating Junction Temperature	-55 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature	-55 to +150	$^{\circ}\text{C}$

Electrical Characteristics @ 25 $^{\circ}\text{C}$ Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
OFF CHARACTERISTICS				
V_F	Forward Voltage ($I_F=100\text{mA}$)	---	1.2	Vdc
I_R	Reverse Current ($V_R=80\text{Vdc}$)	---	0.5	μA
C_T	Capacitance Between Terminals ($V_R=0.5\text{Vdc}$, $f=1.0\text{MHz}$)	---	2.0	pF
t_{rr}	Reverse Recovery Time ($V_R=6.0\text{Vdc}$, $I_F=10\text{mA}$, $R_f=50\Omega$)	---	4.0	ns

Note: 1. Lead in Glass Exemption Applied, see EU Directive Annex 5.

1SS133



Micro Commercial Components




Fig. 1 Forward characteristics




Fig. 2 Reverse characteristics




Fig. 3 Capacitance between terminals characteristics




Fig. 4 Reverse recovery time characteristics




Fig. 5 Surge current characteristics




Fig. 6 Reverse recovery time (t_r) measurement circuit

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 10Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/AmmoBox
Part Number-BP	Bulk: 100Kpcs/Carton

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.