


PIN RECEPTACLES

FOR 0,51 - 0,81 DIAMETER PINS

0338

0338-0-15-XX-15-XX-10-0


Solder mount in 1,45 min. mounting hole
Also available on 12mm wide carrier tape:
1,700 parts per 330mm reel
Order as: 0338-0-57-XX-15-XX-10-0



0378

0378-0-15-XX-15-XX-10-0


Solder mount in 2,08 min. mounting hole



6002

6002-0-19-XX-15-XX-10-0


Solder mount in 1,5 min. mounting hole
Wire Crimp Termination. Accepts wire
sizes 26 AWG Max. / 30 AWG Min.



7009

7009-0-19-XX-15-XX-10-0


Press-fit in 1,6 min. mounting hole
Wire Crimp Termination. Accepts wire
sizes 22 AWG Max. / 26 AWG Min.



0339

0339-0-15-XX-15-XX-10-0

Solder mount in 1,45 min. mounting hole



SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Millimeters

Tolerances On: Lengths: $\pm 0,13$
Diameters: $\pm 0,051$
Angles: $\pm 2^\circ$



ORDER CODE: XXXX - X - 1X - XX - 15 - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#15 CONTACT (DATA ON PAGE 254)

(For alternate contact choices, see group K on page 248)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com